



AZ 07 K 08106

- Single wire entry
- Thermoplastic enclosure
- Contact pin in actuator bridge
- 1 Actuating planes
- Protection class IP20
- transparent cover
- fixing screws M4 undetachable, captive
- Fitting dimensions suitable for AZ 06x
- Self-cleaning through the frictional movement of the contact bridges
- Enclosure with mounting slots

Data

Ordering data

Product type description	AZ 07 K 08106
Article number (order number)	101195819
EAN (European Article Number)	4030661362809
eCl@ss number, version 12.0	27-27-06-10
eCl@ss number, version 11.0	27-27-06-10
eCl@ss number, version 9.0	27-27-06-10
ETIM number, version 7.0	EC002592
ETIM number, version 6.0	EC002592

Approvals - Standards

Certificates

TÜV

General data

Standards	EN 81-20 EN 81-50
Housing material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Material of the housing cover	transparent thermoplastic, self-extinguishing
Gross weight	30 g

General data - Features

Suitable for elevators	Yes
Number of safety contacts	1

Mechanical data

Actuating panels	1
Mechanical life, minimum	1,000,000 Operations
Actuating stroke	7 mm
Actuating force, approx.	1.6 N
Mounting	Fine-adjustment through slotted holes

Mechanical data - Connection technique

Cable entry	Single wire entry
Termination	Screw terminals M20 x 1.5

Mechanical data - Dimensions

Width	72 mm
Height	22 mm
Depth	19 mm

Ambient conditions

Degree of protection	IP20
Ambient temperature	-15 ... +70 °C
Relative humidity, maximum	95 %

Note (Relative humidity)

non-condensing

Ambient conditions - Insulation values

Rated insulation voltage U_i 500 V

Electrical data

Thermal test current 4 A

Utilisation category AC-15 230 VAC

Utilisation category AC-15 2 A

Utilisation category DC-13 200 VDC

Utilisation category DC-13 2 A

Switching element Opener (NC)

Switching principle Self-cleaning pressure contact

Material of the contacts, electrical Silver-plated Cu rivets

Scope of delivery


Scope of delivery Actuator must be ordered separately.

Note

Note (General) The connecting screws can be sealed with plugs. (2 plugs per switch)

Pictures

Product picture (catalogue individual photo)




ID: kaz06f01

| 449.3 kB | .jpg | 303.389 x 240.594 mm - 860 x 682 px - 72 dpi

| 37.2 kB | .png | 74.083 x 58.914 mm - 210 x 167 px - 72 dpi

| 64.5 kB | .jpg | 123.472 x 98.072 mm - 350 x 278 px - 72 dpi

Dimensional drawing basic component



ID: 1az07g01

| 42.2 kB | .cdr |

| 10.0 kB | .png | 74.083 x 51.506 mm - 210 x 146 px - 72 dpi

| 123.2 kB | .jpg | 352.778 x 245.181 mm - 1000 x 695 px - 72 dpi

Schmersal Ltd., Sparrowhawk Close, WR14 1GL Malvern

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 21/08/2024, 09:39